



A concentrate of low-foaming detergents, wetting agents and solvents for use in steam extractor machines to remove grease and grime from rugs and carpets.

Directions: For normal cleaning use 2-3 ounces per gallon of water. Use 150° F water. Follow instructions of machine manufacturer.

The Quality Chemical Company 
VentureTECH
CORPORATION
10720 Lexington Drive • Knoxville, TN 37932
(865) 966-2532 • 1-800-826-4095 • FAX (865) 675-2532

SUPER CARPET EXTRACT

CARPET CLEANER
Low Foaming Concentrate

WARNING: Harmful if Swallowed: Irritant to mouth, throat, esophagus and stomach. **Avoid Breathing Dust or Mists:** Irritant to mucous membranes of the respiratory tract. **Avoid Eye Contact:** Irritant to eye tissues. **Avoid Contact with Skin:** Irritant to all skin tissues. **PERSONAL PROTECTION:** Wash thoroughly after use. Use with adequate ventilation. Chemical type goggles recommended. Impervious rubber or neoprene gloves recommended. **First Aid:** **INHALATION-**Get to fresh air. **EYES-**Flush with plenty of water for at least 15 minutes. See a physician. **INGESTION-** Do not induce vomiting. If conscious drink plenty of water. Call a physician or poison control center immediately. **SKIN-**Flush with plenty of water. READ THE MATERIAL SAFETY DATA SHEET (MSDS) BEFORE USING THIS PRODUCT.

KEEP OUT OF REACH OF CHILDREN

MEMBER
ISSA

HMIS RATING

Health Hazard	0	Fire Hazard	0	Reactivity	0
---------------	---	-------------	---	------------	---

0 - None
1 - Slight
2 - Moderate
3 - High
4 - Severe