



A tough, durable undercoat that seals the pores in all vinyl, rubber, linoleum, asphalt and concrete floor surfaces **DURA SEAL** bonds to the floor surface, smooths and levels imperfections in surface. **DURA SEAL** improves adhesion of final floor finish. Non-yellowing.

Clean floor thoroughly with a good wax stripper. Rinse well and allow to dry completely. Apply **DURA SEAL** with a clean mop or a lambs wool applicator allow to dry for 30 minutes then apply additional coats if desired. Two or Three coats may be required depending on the porosity of floor.

The Quality Chemical Company 
VentureTECH
CORPORATION
10720 Lexington Drive • Knoxville, TN 37932
(865) 966-2532 • 1-800-826-4095 • FAX (865) 675-2532

DURA SEAL

FLOOR SEALER

Floor finishing results in temporarily slippery surfaces. To prevent falls protect wet areas with appropriate warning signs and barriers.

WARNING: Harmful if Swallowed: Irritant to mouth, throat, esophagus and stomach. **Avoid Breathing Dust or Mists:** Irritant to mucous membranes of the respiratory tract. **Avoid Eye Contact:** Irritant to eye tissues. **Avoid Contact with Skin:** Irritant to all skin tissues. **PERSONAL PROTECTION:** Wash thoroughly after use. Use with adequate ventilation. Chemical type goggles recommended. Impervious rubber or neoprene gloves recommended. **First Aid: INHALATION-**Get to fresh air. **EYES-**Flush with plenty of water for at least 15 minutes. See a physician. **INGESTION-**Do not induce vomiting. If conscious drink plenty of water. Call a physician or poison control center immediately. **SKIN-**Flush with plenty of water. READ THE MATERIAL SAFETY DATA SHEET (MSDS) BEFORE USING THIS PRODUCT.

KEEP OUT OF REACH OF CHILDREN

MEMBER
ISSA

HMS RATING

Fire Hazard	0
Health Hazard	1
Reactivity	0

0 - None
1 - Slight
2 - Moderate
3 - High
4 - Severe