



A tough, durable undercoat that seals the pores in all vinyl, rubber, linoleum, asphalt and concrete floor surfaces. **DURA STONE** bonds to the floor surface, smooths and levels imperfections in surface. **DURA STONE** improves adhesion of final floor finish. **Non-yellowing.**

**DIRECTIONS:** Clean floor thoroughly with a good wax stripper. Rinse well and allow to dry completely. Apply **DURA STONE** with a clean mop or a lambs wool applicator; allow to dry for 30 minutes, then apply additional coats of finish if desired. Maintain by damp mopping with a neutral floor cleaner.

The Quality Chemical Company   
**VentureTECH**  
CORPORATION  
10720 Lexington Drive • Knoxville, TN 37932  
(865) 966-2532 • 1-800-826-4095 • FAX (865) 675-2532

# DURA STONE

## CONCRETE SEALER

*Floor finishing results in temporarily slippery surfaces. To prevent falls protect wet areas with appropriate warning signs and barriers.*

**WARNING:** Harmful if Swallowed: Irritant to mouth, throat, esophagus and stomach. **Avoid Breathing Dust or Mists:** Irritant to mucous membranes of the respiratory tract. **Avoid Eye Contact:** Irritant to eye tissues. **Avoid Contact with Skin:** Irritant to all skin tissues. **PERSONAL PROTECTION:** Wash thoroughly after use. Use with adequate ventilation. Chemical type goggles recommended. Impervious rubber or neoprene gloves recommended. **First Aid: INHALATION-**Get to fresh air. **EYES-**Flush with plenty of water for at least 15 minutes. See a physician. **INGESTION-**Do not induce vomiting. If conscious drink plenty of water. Call a physician or poison control center immediately. **SKIN-**Flush with plenty of water. **READ THE MATERIAL SAFETY DATA SHEET (MSDS) BEFORE USING THIS PRODUCT.**

**KEEP OUT OF REACH OF CHILDREN**

MEMBER  
**ISSA**

**HMS RATING**

0	Fire Hazard
1	Health Hazard
0	Reactivity

0 - None  
1 - Slight  
2 - Moderate  
3 - High  
4 - Severe