



DIRECTIONS: **1.** For light-duty stripping, mix 1 part of RENEW with 10 parts of hot water. Where wax build-up is excessive, it may be necessary to use stronger concentrations. **2.** Spread solution with cloth, sponge or mop thoroughly wetting floor. Apply liberally around room edges & heavy traffic areas. **3.** Leave solution on floor 4-5 minutes. Machine scrub to remove softened wax. Wipe floor thoroughly clean. Do not allow solution to dry before mopping or wiping up loosened wax. **4.** Rinse floor thoroughly with clean water. Let dry.

RENEW

NON-AMMONIATED WAX STRIPPER

RENEW is a special combination of chemical ingredients for stripping away old layers of scuffed, dirt-embedded, and yellowed wax from linoleum, asphalt & rubber tile, vinyl & other non-wood surfaces.

WARNING: Harmful if Swallowed: Irritant to mouth, throat, esophagus and stomach. **Avoid Breathing Dust or Mists:** Irritant to mucous membranes of the respiratory tract. **Avoid Eye Contact:** Irritant to eye tissues. **Avoid Contact with Skin:** Irritant to all skin tissues. **PERSONAL PROTECTION:** Wash thoroughly after use. Use with adequate ventilation. Chemical type goggles recommended. Impervious rubber or neoprene gloves recommended. **First Aid: INHALATION-**Get to fresh air. **EYES-**Flush with plenty of water for at least 15 minutes. See a physician. **INGESTION-** Do not induce vomiting. If conscious drink plenty of water. Call a physician or poison control center immediately. **SKIN-**Flush with plenty of water. READ THE MATERIAL SAFETY DATA SHEET (MSDS) BEFORE USING THIS PRODUCT.

KEEP OUT OF REACH OF CHILDREN

The Quality Chemical Company 
VentureTECH
CORPORATION

10720 Lexington Drive • Knoxville, TN 37932
(865) 966-2532 • 1-800-826-4095 • FAX (865) 675-2532

MEMBER
ISSA

HMIS RATING

Health Hazard	1	0	Fire Hazard	0	0	Reactivity	0
							0 - None 1 - Slight 2 - Moderate 3 - High 4 - Severe